

COMFORT GRIP CONNECTOR

- Transverse load rated self-locking/closing aluminum Comfort Grip connector
- Built-in connector for single-leg SRL direct attachment to harness
- Extremely compact, lightweight design
- Tough and impact-resistant thermoplastic housing
- Swiveling anchorage loop
- Quick-activating speed-sensing brake system
- High-capacity external energy absorber and impact indicator
- i-Safe™ equipped
- Certification: CSA standard Z259.12 for transverse loading
- Note that this connector pairs with many of 3M lanyards and SRLs so multiple configurations are available

Model No. SGJ693
Mfg. No. 1246415
Price/Each \$



CONCRETE DETENT ANCHORS

- Reusable detent pin assembly allows a user to tie-off anywhere a socket is pre-installed with a push of a button
- Lightweight and portable
- Socket can be installed vertically or overhead into a concrete wall, floor, or ceiling
- Rugged, corrosion resistant stainless steel

Model No. SEJ623
Mfg. No. 2101004
Price/Each \$



CABLE TIE-OFF ADAPTORS

- 1/4" coated galvanized cable
- Lightweight and extremely durable
- Stands up to harsh environments
- Snap hook at one end, O-ring at the other
- Length: 6'

Model No. SEB470
Mfg. No. AJ408CG-6
Price/Each \$



CARABINERS

- Steel carabiners
- Self locking/closing
- 3600-lb. gate



Model No.	Mfg. No.	Gate Opening"	Price /Each
SEH168	2000117	25/32	
SEE719	2000113	1-3/16	

ANCHORAGE CONNECTING CARABINER

- High strength steel construction
- Corrosion resistant zinc plated hardware
- 11/16" gate opening
- 420 lbs. capacity
- 3600 lbs. gate strength
- Self-closing and locking gate for added safety

Model No. SEB926
Mfg. No. 2000112
Price/Each \$



CONCRETE D-RING ANCHORS

- Reusable D-ring assembly
- Rugged design for harsh environments
- Safe "hook-up" indicator notifies user of proper installation
- Install into 11/16" or 3/4" holes - only standard drill bits needed

Model No. SEB438
Mfg. No. 2104568
Price/Each \$



TIE-OFF ADAPTORS

- Pass-thru style polyester web tie-off adaptor



Model No.	Mfg. No.	Length'	Price /Each
SEB389	1003000	3	
SEB390	1003006	6	

D-RING ANCHORAGE PLATES

- Can be bolted or welded to a structure, offering a compact, reliable connection point
- Two 1/2" diameter attachment holes
- Cadmium plated steel D-ring
- 304 stainless steel anchorage plate
- Plate size: 1/4" x 2" x 4 1/2"

Model No. SEB449
Mfg. No. 2101639
Price/Each \$

