

LADDERS & SCAFFOLDING

INDUSTRIAL HEAVY-DUTY ALUMINUM EXTENSION/STRAIGHT LADDERS

CSA grade 1A,
ANSI type 1A – 300-lb. Load Rating

- Heavy-duty "C" channel construction
- Side rails: 2 1/2" x 1" for straights up to 14'
- Side rails: 3" x 1" for straights up to 16' and up
- Heavy-duty serrated "D" rungs prevent slipping for safe and sure climbing
- Black ABS, high impact, non-marking end caps
- Heavy-duty safety shoes

FEATHERLITE
INDUSTRIAL LADDERS

VC276

VC322



INDUSTRIAL HEAVY-DUTY ALUMINUM EXTENSION/STRAIGHT LADDERS

CSA grade 1A,
ANSI type 1A - 300-lb. Load Rating

- Rigid box section side rails, unequalled for strength and durability
- Side-mounted rope pulley and slide guide system keeps rope clear of climbers feet and allows easy raising (only on 4200D Series)
- Yellow ABS, high impact non-marring end caps
- Premium heavy-duty rung locks (Only 4200D Series)
- Slip-resistant serrated "D" rungs for safe climbing and comfort (round rung on 4100 Series)
- Heavy-duty ribbed swivel feet with ice pick



Series 4100

Series 4200D

FEATHERLITE
INDUSTRIAL LADDERS

Model No.	Nominal Length'	Working Length"	Outside Width"	Wt. lbs.	Price /Each
STRAIGHT LADDERS (3100D SERIES)					
VC273	8	-	17 3/4	12	
VC274	10	-	17 3/4	14	
VC275	12	-	17 3/4	18	
VC276	14	-	17 3/4	21	
VC277	16	-	17 3/4	24	
VC278	18	-	17 3/4	27	
VC279	20	-	17 3/4	30	
EXTENSION LADDERS (3200D SERIES)					
VC322	16	13	17 3/4	31	
VC323	20	17	17 3/4	36	
VC324	24	21	17 3/4	43	
VC325	28	25	17 3/4	51	
VC326	32	29	17 3/4	58	
VC327	36	32	17 3/4	69	
VC328	40	35	17 3/4	77	

Model No.	Nominal Length'	Working Length'	Outside Width"	Wt. lbs.	Price /Each
STRAIGHT LADDERS (4100 SERIES)					
MD506	8	-	14 5/8	13	
MD507	10	-	14 5/8	16	
MD508	12	-	14 5/8	19	
MD509	14	-	14 5/8	22	
MD510	16	-	14 5/8	25	
MD511	18	-	14 5/8	28	
MD512	20	-	14 5/8	31	
MD513	22	-	15 3/4	41	
MD514	24	-	15 3/4	44	
EXTENSION LADDERS (4200D SERIES)					
VC033	16	13	17	29	
VC034	20	17	17	37	
VC035	24	21	17	44	
VC036	28	25	17	50	
VC037	32	29	18 1/2	69	
VC038	36	32	18 1/2	78	
VC039	40	35	18 1/2	86	
VC040	44	39	18 1/2	94	

The following three causes are responsible for over 94% of all ladder accidents:

- A person overreaches and the ladder tips sideways
- A person does not transfer their weight properly when moving from a roof to the ladder, resulting in the ladder falling
- The base of the ladder slips outward while someone is standing on the ladder

INDUSTRIAL EXTRA HEAVY DUTY MULTI-PURPOSE JAWS™ TELESCOPIC LADDERS

CSA grade 1AA, ANSI type 1AA-375-lb. Load Rating

- Compact and multifunctional, replaces all conventional ladders
- Easily folds for storage or transport
- Flared ends with slip-resistant feet provide superior stability in any position
- Polymer rung locks are virtually indestructible
- Welded outer rungs
- Extra deep side rails make the Jaws™ stiffer and stronger
- Mechanical interlocking tooth hinges for superior strength and 5 locking positions
- Extruded 6061-T6 marine alloy for strength and corrosion resistance
- JLT Series has extra-strong "Box-beam" rails for maximum strength and durability



MEETS OR EXCEEDS
ANSI
14.2 STANDARD
WHERE APPLICABLE

FEATHERLITE
INDUSTRIAL LADDERS

HIGH PERFORMANCE TELESCOPING CLIMBING SYSTEM

Model No.	Folded Height	Extension Range'	Stepladder Range'	Scaffold Height'	Wt. lbs.	Price /Each
MA740	4.75'	9 to 15	4.5 to 7.5	1 to 4	36	
MA741	5.75'	11 to 19	5.5 to 9.5	1 to 5	41	
MA742	6.75'	13 to 23	6.5 to 11.5	1 to 6	50	