

CHEMICALS



LU204 DRY FILM GRAPHITE LUBRICANT

- Ideal where a dry lubricant is or where petroleum products must be avoided
- Adheres with minimum pre-treatment
- Effective up to 850°F constant and 1000°F intermittent
- Dries rapidly at room temperature
- For pre-assembly lubrication of moving parts, mechanisms of vending machines and parking meters, automotive and industrial gaskets, bearings, locks, springs, hinges, mating surfaces on machines, CRT's, plating non-conductors, curing ovens



Model No.	Mfg. No.	Size	Price /Each
AA107	SC0204000	10 oz.	

DRY FILM SILICONE LUBRICANT

- Colourless, thin film
- Excellent for releasing moulded parts in high temperatures or pressures
- Low odour
- Non-staining
- Non-flammable
- Non-corrosive



Model No.	Mfg. No.	Size	Price /Each
AA902	C01616	11 oz.	

LU708 HIGH PERFORMANCE DRY LUBRICANT

- Dry, non-oily, non-staining lubricant
- Made with DuPont® Krytox®
- Dries quickly to a white, chemically inert film
- Effective from -40°F to 572°F
- Resists most solvents
- For metal extrusions, munitions, locks and catches, window guides, synthetic fibers, machine parts, cord, twine or rope, leather drawers, hinges, paper, glass, elastomers and some plastics
- Use as release agent on conveyor belts, chutes and slides, industrial blenders, tanks, bins and spray booths



Model No.	Mfg. No.	Size	Price /Each
AA184	SC0708000	10 oz.	

DETEX® HEAVY DUTY SILICONE LUBRICANT

- A silicone-rich, water-based lubricant that eliminates sticking, binding, and squeaking while protecting rubber and plastic parts
- NSF H1 lubricant can be used anywhere within a facility where incidental food contact may occur
- Safe on most surfaces, including rubber and plastics
- Odourless formula reduces potential transference to foods
- Colourless lubricant will not stain production equipment
- Metal and X-ray detectable packaging
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AH203	C51516	369 g	

DETEX® FOOD GRADE SILICONE LUBRICANT

- Anti-stick agent for chutes and slides to keep packages moving
- NSF H1 lubricant can be used anywhere within a facility where incidental food contact may occur
- Dry film will not attract dust or dirt
- Safe on all metals, plastics, and rubber part
- Colourless formula will not stain packaging material or equipment
- Metal and X-ray detectable packaging
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AH211	C01716	284 g	

LU200 DRY MOLY LUBRICANT

- Penetrates pores of substrate and bonds to surface for long-lasting lubrication
- High-pressure, high-solids molybdenum disulfide coating
- Withstands pressures up to 50 000 PSI
- Air dries in 5-10 minutes; cures in 2 hours at room temperature
- Maintains effectiveness under high temperatures (650°F constant and 750°F intermittent)
- For assembly and run-in lubrication, automotive and industrial gaskets, sliding surfaces and gears, chutes and bins, bearings, chain drives, intricate mechanisms, vending machines, parking meters, roller chains, conveyor belts where heat is present



Model No.	Mfg. No.	Size	Price /Each
AA104	SC0200000	11 oz.	

FORCE 842® DRY MOLY LUBRICANT

- Works under high temperatures up to 842°F (450°C) and pressures up to 100 000 PSI (6890 bars)
- Prevents seizure of parts
- High adhesion
- Resists dust and dirt
- Water and chemical resistant
- Provides a quick drying, thin film
- Not recommended for friction bearings or light-duty bearings



Model No.	Mfg. No.	Size	Price /Each
AA845	C02516	11 oz.	

MAGNUM PREMIUM LUBRICANT WITH PTFE

- High performance lubricant with PTFE additives
- Ultra high lubricity
- Penetrates and protects metal against rust and corrosion
- Flash point of 175°F (79°C)
- Displaces moisture
- Safe to use on most surfaces
- Inverta Spray Valve lets you spray in all directions
- NSF registered category code H2



Model No.	Mfg. No.	Size	Price /Each
AA842	C00616	11 oz.	

POWER LUBE W/PTFE

- Maximum Working Temperature: 300°F (148.9°C)
- Contains PTFE for long-lasting lubrication and protection
- High performance
- NSF Registered H2



Model No.	Mfg. No.	Size	Price /Each
AF239	73045	312 g	