

## FUME EXTRACTOR ARMS

- An extractor arm extracts smoke, dust and gases directly at the source, before the contamination has spread in the premises and been inhaled
- Superior extraction arm and advanced design "Parallelogram" counter balancing system that eliminates the need for continual adjustment of friction joints and allows for an unparalleled ease of movement
- Ideal solution for most "source-capture" applications and specifically recommended for applications requiring an "easy to position" extractor that does not require constant adjustment
- Compact and smooth design, clearance of 1m (50") required
- **5-year limited warranty**

**Flexi construction:** Internal supporting mechanism made of mild steel tubing, 3 spring-assisted joints to provide precise counterbalancing of the extractor's inner and outer arm. Comes with a black baked-on enamel steel hood w/ optimized airflow and ring handle, and built in damper and with black baked-on enamel wall bracket. Motor and fan not included.

levco



### EXTRACTOR ARMS

Description	Flexi I, 6.5" dia Model No.	Mfg. No.	Price /Each	Flexi II, 8" dia Model No.	Mfg. No.	Price /Each
7' (2 m) Extractor Arm w/Wall Bracket	BA660	P-007		BA978	P-143	
10' (3 m) Extractor Arm w/Wall Bracket	BA661	P-008		BA979	P-144	
14' (4 m) Extractor Arm w/Wall Bracket	BA662	P-009		BA980	P-145	
17' (5 m) Extractor Arm w/Wall Bracket	BA663	P-010		BA985	P-146	

## MINI-FLEX

### MINI FLEX DUAL HOSE MOUNT

- "At source" fume collector designed for soldering, TIG welding and other toxic applications
- The compact design ensures convenient mobility and features 2 flexible extractor arms that retain their position to source capture fume and gases before entering the operators breathing zone
- Easily mounted on top or just underneath a table (Tabletop would require two 3.5" diameter holes)

### CONSTRUCTION:

- 16/18 ga. welded steel cabinet with white finish
- Filter access through top assembly
- ON/OFF rocker switch
- 2.5 m (8') long power cord
- Running light
- Acoustical silencing foam
- 200 Watt motor, 115/1/60Hz (0.85 amps),
- 1" poly prefilter, 99.97% HEPA filter, 1" charcoal filter,
- Two 42" fume extractor arms with aluminum hoods
- 12" L x 13" W x 20" H
- **5-year limited warranty**
- Always refer to owners manual before operating this type of equipment

### FEATURES & BENEFITS:

- Light extraction arms - Easy to set into position above the process
- Compact design - Place directly on or below the work surface/table
- 3 stage filtration: Prefilter, HEPA and charcoal - Allow the unit to be used for a variety of applications
- High flow rate (300 CFM) - Capture fumes before they reach the operators breathing zone



levco

Model No.	Mfg. No.	Description	Price /Each
EA448	MINI-FLEX	Mini-Flex Dual Hose Mount	

KLETON

CANADA'S LEADING MATERIAL HANDLING SUPPLIER

